

INDOOR WOOD CARE

TRANSLUCENT



1. PRODUCT DESCRIPTION

1.1	Product type	Wood care / Indoor wood paint
1.2	Manufacturer	PPG/Dyrup, Gladsaxevej 300, DK-2860 Søborg, Denmark. Tel.: +45 39 57 93 00 - www.bondexwood.com
1.3	Where to use	Indoor wooden surfaces, e.g. walls, ceilings, skirting boards, door frames and furniture.
1.4	Colour range	• 100 Base 30 • 800 White
1.5	Form supplied	Ready to use
1.6	Can sizes	0.75 L

2. COMPOSITION

2.1	Binder	Acrylic.
2.2	Solvents	Water.

3. TECHNICAL DATA

3.1	Specific gravity	App. 1.02 g/l.
3.2	Viscosity	Thixotropic - 80 sec. DIN cup 4 mm.
3.3	Flash point	Non flammable.
3.4	Gloss	App. 25 at a 60° angle.
3.5	Solid content	App. 11.9-17.2 W/W%
3.6	Special qualities	Good flow qualities, refreshes yellowed wood. Tintable in many translucent colours.
3.7	Odour	Weak.
3.8	Coverage	8-10 m ² , depending on the substrate.
3.9	Drying time	Touch dry: app. 1 hour. Recoatable: app. 4 hours. Through dry: app. 4 weeks. Measured at 23° and normal humidity (60%). Deviations may occur by change in temperature, humidity and layer thickness.

3.10	Storage	Store and transport dry, cool and frost-free and out of direct sunlight in tightly closed container.
3.11	Shelf life	3 years in unopened container. Limited shelf life after opening.

4. SURFACE & PREPARATION

4.1	In general	Stir before use. Mix different batch numbers in order to avoid colour- and gloss difference. Keep the container firmly closed after use. Read label and instructions before application.
4.2	Substrate	The substrate must be clean, dry and solid.

5. TREATMENT

5.1	Pre-treatment	Loose fibres must be removed mechanically. Clean the surface with a suitable detergent. If you intend to use light colours, you should prime yellowed wood and water stains. The cause of the water stains should be remedied.
5.2	Treatment	Apply 2-3 coats of Bondex Indoor Wood Care. If you have applied a primer as the first coat, it will normally be sufficient to apply 1 coat of Bondex Indoor Wood Care. Apply the product along the wood grain.
5.3	Maintenance	As and when needed.
5.4	Dilution	Water.
5.5	Cleaning of tools	Soap and water.

6. SAFETY PRECAUTIONS

6.1	In general	Common safety rules for work with paints and varnishes must be observed. Further information is available from our Material Safety Data Sheet.
-----	------------	--

7. GOOD ADVICE

7.1	Good advice	Do not empty into drains or into the environment. Product waste must not be poured into the sewers, water reserves or soil. Empty can may be recycled (check with your local waste disposal site or your local authorities).
-----	-------------	--

The purpose of this Technical Data Sheet is to provide our clients with information about the properties and characteristics of the product. The information provided is based on tests conducted by us under usage conditions that comply with the prevailing standards. Our recommendations for use are for information only, and in no event shall they take precedence over any specific recommendation, taking into account the nature and conditions of a particular site, nor shall they engage PPG's liability. Before all applications of the product, clients should check that this document has not been amended by a more recent version, which takes into account new technical data. This version annuls and replaces all previous versions of Technical Data Sheets relating to this product.