



SIGMA VIKOTE™ 56

Fast-drying acrylic finish – above-water protection

- Cost-effective finish with excellent anticorrosive protection
- Excellent aesthetics through good gloss and color retention
- Fast drying and trouble-free application
- Resistant to splash and spillage of mild chemicals
- For the protection of decks, superstructure and topsides
- Can be applied down to -10°C (14°F)
- Suitable for application at new-building, in dry dock or for onboard maintenance
- Extensive range of colors available through our color network centers
- Part of the SIGMACARE® onboard maintenance service



**PPG Protective &
Marine Coatings**

Bringing innovation to the surface.™

SIGMA VIKOTE™ 56

Fast-drying acrylic finish – above-water protection

An easy to apply maintenance solution with good aesthetics

Vessel maintenance is one of the main concerns for ship operators worldwide. There is a good reason for this: well-maintained ships that are aesthetically pleasing communicate to prospective charterers that the vessel is more likely to accommodate their needs in a professional and safe manner.

Accordingly, fast and economical onboard maintenance plays an important role in maintaining this good image. In the current economic climate, ship operators must achieve this objective with limited crews and tight budgets.

SIGMA VIKOTE 56 is an excellent, easy-to-apply, economical finish coat that fits this scenario perfectly and helps to present a good corporate image whilst protecting the asset.

The quality of finish, flexibility and simplicity makes *SIGMA VIKOTE 56* an excellent choice for all above-water maintenance projects.

Fast-drying finish – economical and flexible maintenance applications

SIGMA VIKOTE 56 is a fast-drying, modified acrylic finish, which is ideal for all decks, superstructure, and topsides. The system is very easy to apply by airless spray, brush or roller and is compatible with most existing paint systems

It exhibits fast drying and offers short minimum overcoating times permitting onboard maintenance projects to progress at a rapid pace. Application is straightforward even at temperatures down to -10°C (14°F) leaving a finish that offers good resistance to weathering, general wear and tear, and mild chemical splash and spillage.

SIGMA VIKOTE 56 finish provides good protection properties, high levels of aesthetic appeal, and easy application.

Extensive color range – supplied around the globe

SIGMA VIKOTE 56 finish offers good color and gloss retention and comes in an extensive range of colors available through our worldwide color network centers.

Features

- Cost-effective, easy to apply finish
- Suitable for application at new-building, in the dry dock or for onboard maintenance
- Excellent aesthetics through good gloss and color retention
- Fast drying and trouble-free application
- Resistant to splash and spillage of mild chemicals
- For the protection of decks, superstructure and topsides
- Can be applied down to -10°C (14°F)

Benefits

- Cost-effective onboard maintenance – improved profitability
- Flexibility of use – simplifies stock lists
- Easy to apply – less time, more productivity
- Fast drying – reducing maintenance downtime
- Good gloss retention - easier cleaning
- Reliable and proven track record
- Available in any color of choice supplied through our global color network centers
- Supported by SIGMACARE® crew support and training package

For good aesthetics and efficient onboard maintenance – choose *SIGMA VIKOTE 56* finish.